

Microwave Leakage Tester MLT 5

- Handheld-instrument
- LED-scale, 11 graduations
- Supplied with calibration certificate
- Digitally scanning of the E-field
- Determination of the effective value of the power density
- Improved rotation symmetry and directional characteristics
- Self-test after each power-on
- Acoustic signal at over-ranging
- Battery low indicator LED
- Working with 2 standard LR6 AA batteries



The model MLT 5 is a modern testing instrument to find microwave fields. The easy handling gives security in dealing with microwave sources. As the consistent further development of the MLT 4 it combines the proven easy handling with the opportunities offered by modern technology.

The core is a microcontroller. It scans the measurement signal digitally and calculates the effective value of the power density. The internal step-up converter allows the usages of two standard mignon batteries to supply the MLT 5. The usage of rechargeable batteries is also possible.

The MLT 5 is an indispensable instrument to control the security on microwave ovens.

It is supplied in a practical transport case. So the device is always well protected.



Microwave Leakage Tester MLT 5

Technical Data:

Range:

Type 02 0... 2mW/cm²
Type 05 0... 5mW/cm² non linear
Type 10 0...10mW/cm²

Precision:

+/- 1 db
calibrated at 2450 MHz or 915 MHz

Power:

Batteries 2x 1,5 V LR6 AA
approx. 1000 measurements with a battery set

Power density:

Max. 1,0W/cm²

Dimension (mm):

Case: 120x65x40
Total: 240x65x50

Operating temperature:

10 °C to 40 °C

Weight:

155 g without batteries
200 g with batteries

Rotation symmetry:

Difference max. +/- 3 %

Directional characteristics:

